

ADB 2721WX

HIGH DEFINITION IPTV DIGITAL VIDEO RECORDER

FEATURES

- Smooth-View™ HD replay in slow and fast motion with audio
- Ready for advanced home networking and over-the-top services
- HTML5 browser with HTTP Live Streaming (HLS) for optimal over-the-top delivery
- SD card reader to play out home videos and photos
- Latest dual-core technology for a blazing fast user experience and full 1080P

TECHNICAL SPECIFICATIONS

TELEVISION STANDARDS

- PAL/NTSC

SYSTEM RESOURCES

- Hard disk: 320 GB
- CPU power: 1100 DMIPS
- DDRAM: 512 MB
- NAND Flash: 128 MB

SOFTWARE

- Operating system: Linux
- Browser: Webkit
- Middleware: Minerva, Ericsson IAP (others upon request)
- Conditional access: Verimatrix, Widevine, Latens
- Copy protection: HDCP 1.2, Macrovision 1.01, CGMS-A
- TR069 / TR135



BACK PANEL

- 2 x RCA (audio L/R)
- 1 x HDMI
- 1 x SPDIF (optical)
- 1 x Ethernet 10/100 Mbps
- 1 x USB 2.0
- 3 x RCA (YPbPr)

FRONT PANEL

- 3 x LED
- 1 x USB 2.0
- 1 x SD card reader

RESIDENT APPLICATIONS

- UPnP media player
- Picture-in-picture
- Home networking (DLNA)

TECHNICAL SPECIFICATIONS

VIDEO

- MPEG-2: MP@ML & MP@HL
- MPEG-4.10 H.264: MP@L3.1, HP@L4.1 (AVC/H.264)
- MPEG-4.2 H.264: ASP
- VC-1/WMV9: MP@LL, MP@ML, MP@HL, SP@LL, SP@ML
- SMPTE VC-1 SP@LL, MP@LL, MP@HL, AP@L1-3
- Support of Xvid, MKV and DivX
- Downscaling HD video onto SD output
- Resolution: up to 1080P
- 32-bit color display

AUDIO

- MPEG-1 Layer 3 (MP3): up to 320 kbps, 32/44, 1/48 kHz
- MPEG-2 Layer 2
- HE_AAC
- AC3 (Dolby Digital) pass-through and down-mix to stereo
- WMA9
- Dolby Digital Plus pass-through to external decoder
- Dolby Digital Plus down-mix

CERTIFICATIONS & CONFORMITIES

- RoHS
- HDMI 1.3a
- Dolby Digital
- CE Marking
- CoC v8
- FCC, UL & CUL

PERFORMANCE

- Deep standby power: <1W
- Standby: 8W (outputs disabled)
- Operating power: 20W (typical)

ACCESSORIES

- Power Cord with PSU
- Quick Install Manual
- Remote Control and batteries (opt.)
- Audio/Video cables (opt.)
- Ethernet cable (opt.)

GENERAL DATA

- Operating temperature range: +5 to 40 (°C)
- AC input voltage: 90 - 264 V, 50/60 Hz
- Dimensions: 292 x 194 x 60 mm (W x D x H)