

ARRIS TG3442SP

DOCSIS® 3.1 GATEWAY WITH WI-FI 5

FEATURES

- 2x2 OFDM and OFDMA DOCSIS® 3.1 channels
- 32x8 SCQAM EuroDOCSIS® 3.0 channels
- Full Capture Bandwidth Tuner
- Switchable diplexer 5-85 MHz or 5-204 MHz
- 4 port Gigabit Ethernet Router
- 3x3 2.4GHz 802.11n
- 4x4 5GHz 802.11ac Wave 2
- USB 3.0 Host Port
- 2 FXS Ports of carrier grade VoIP with HD voice
- Multi Processor Technology for enhanced application support
- Advanced Firmware support for IPV6, DS-Lite, and SoftGRE
- RDK-B Based

PRODUCT SPECIFICATIONS

PHYSICAL

Operating Temperature	0 to 40°C
Operating Relative Humidity	5-85% (non-condensing)
Storage Temperature	-40 to 70°C
Dimensions (H x W x D)	246 mm x 199 mm x 64 mm (excludes 'F' connector)
Weight	0.785kg
Diagnostic LEDs (Front)	PHONE, INTERNET, WPS, WIFI, POWER
Diagnostic LEDs (Rear)	Ethernet Link/Speed
Front Switches	WPS, WIFI On/Off, Power On/Off

INTERFACES

RF Interface	External 'F' type connector
Data Interfaces (bridged)	4 x 10/100/1000 Base-T Ethernet (RJ-45 connector)
Analog Telephony Interface	2 lines; RJ-11
Input Voltage (nominal)	12V DC
Input Current	3.0A





ARRIS TG3442SP

DOCSIS® 3.1 GATEWAY WITH WI-FI 5

PRODUCT SPECIFICATIONS

RF DOWNSTREAM

Bonded Channels	Up to 32 SCQAM and/or 2 OFDM
Tuner Configuration	Full capture tuning range
Frequency Range (MHz)	108-254MHz-1218MHz DOCSIS
Data Rate (Mbps Max.)	Up to 5 Gbps
RF Input Sensitivity Level (dBmV)	-15 to +15 (DOCSIS)

RF UPSTREAM

Bonded Channels	Up to 8 SCQAM and/or 2 OFDMA
Frequency Range (MHz)	5MHz to 85MHz or 5MHz to 204MHz
Data Rate (Mbps Max.)	Up to 1 Gbps
RF Output Level (dBmV)	+65 dBmv (64 QAM, single upstream) +57 dBmv (64 QAM, 4-8 upstreams) +65 dBmv (16 QAM, single upstream) +65 dBmv (OFDMA)

WIRELESS

Frequency Range	2.4GHz and 5GHz
Transmit Power EIRP	+28.0dBm (MCS0, 2.4GHz, HT20) +24.0dBm (MCS7, 2.4GHz, VE20) +30.5dBm (MCS0, 5GHz, VHT20) +25.5dBm (MCS9, 5GHz, VE80)
Spatial Streams	3 for 2.4GHz, 4 for 5GHz
Receive Levels	-92dBm 802.11n (MCS0, 2.4GHz, VE20) -88dBm 802.11ac (MCS0, 5GHz, VE20)



ARRIS TG3442SP

DOCSIS® 3.1 GATEWAY WITH WI-FI 5

PRODUCT SPECIFICATIONS

VOICE

Standards Supported

PacketCable™ NCS (1.5/2.0)
Network-based call signaling protocol
(PKT-SP-EC-MGCP)
RFC 3261 SIP
RFC 2805 MGCP

Codecs Supported

G.711, G.722, G.729ab

FAX

T.38, G.711 Fax Passthrough

REN Capability

5 REN Total

Voice Supplementary Services

Call Waiting
Call Hold
3PTY Call
Caller ID
Voice Activity Detection (VAD) Comfort Noise
Generation (CNG) Echo cancellation:
G.165
G.168 up to 16 ms

DTMF Tone Relay

RFC 2833

Pulse Dialing

DTMF/pulse tones
Pulse/DTMF tones conversion

RTP Layer

RFC 1889
RFC 1890

Line Card Support

Flexible LC Templates