

# ARRIS TM804G

## DOCSIS 3.0 CABLE MODEM

### FEATURES

- DOCSIS® 3.0 compliant
- PacketCable® 1.0 and 1.5 compliant
- Up to 4 lines of carrier-grade VoIP
- Flexible 8x4 downstream/upstream channel bonding
- Backwards compatible with DOCSIS® 1.0, 1.1, and 2.0
- Multiple Protocol Support: PacketCable® (NCS) or Session Initiation Protocol (SIP)
- IPv4 or IPv6 addressing modes for DOCSIS® CM layer



### PRODUCT SPECIFICATIONS

#### PHYSICAL

<b>Operating Temperature °F (°C)</b>	32 to 122 (0 to 50)
<b>Operating Relative Humidity (Min-Max)</b>	5-95% (Non-condensing)
<b>Storage Temperature °F (°C)</b>	-40 to 158 (-40 to 70)
<b>Dimensions (H x W x D) in.</b>	9.7 x 2.1 x 7.1
<b>Weight (lbs.)</b>	1.5 - excluding battery
<b>Battery Back-up 6-Hour Option</b>	Lithium-ion 2.2 AH Capacity, 0.25 lbs Battery
<b>Battery Back-up 12-Hour Option</b>	Lithium-ion 4.4 AH Capacity, 0.50 lbs Battery
<b>Battery Back-up 18-Hour Option</b>	Lithium-ion 6.6 AH Capacity, 0.75 lbs Battery
<b>Battery Back-up 24-Hour Option</b>	Lithium-ion 8.8 AH Capacity, 1.0 lbs Battery
<b>Battery Storage Temperature °F (°C)</b>	-4 to 140 (-20 to 60)
	<i>Note: Storage above 77°F (25°C) reduces battery life</i>
<b>Telemetry</b>	AC Fail, Battery Low, Battery Missing, Replace Battery
<b>Diagnostic LEDs</b>	Power, DS, US, Online, Link, Tel 1, Tel 2, Tel 3, Tel 4, Battery



# ARRIS TM804G

## DOCSIS 3.0 CABLE MODEM

### PRODUCT SPECIFICATIONS

#### INTERFACES

RF Interface	External 'F' type connector
Data Interface	10/100/1000 Base-T Ethernet (RJ-45 connector)
Telephony Interface	4 lines; RJ-14 (Line 1/2, Line 3/4), RJ-11 (Line 2, Line 4)
Input Voltage (nominal)	115-240 VAC 50/60 Hz
Power Consumption (W)	6 (idle), 16 (max.)

#### TELEPHONY

Supervisory Voltage	48 V DC nominal
Maximum Loop Length to CPE	1000 ft (305M) of 26 AWG (0.4 mm) wire
Ringing Load Capacity	10 REN total; 5 per line
Provisionable High Loop Current Mode	Yes
Telcordia™ GR 1089 (Lightning and Power Surge) Tested	Yes
Programmable Interface for Worldwide Applications	Yes

#### RF DOWNSTREAM

Frequency Range (MHz)	108-1002
Bonded Channels	Up to 8
Number of Tuners	2
Capture Bandwidth (MHz)	96 (per tuner, 192 MHz total)
Modulation (QAM)	64 or 256
Data Rate (Mbps Max.)	Up to 343
RF Input Sensitivity Level (dBmV)	-15 to +15
Carrier Bandwidth	6 MHz
MoCA® Immunity Filter	Yes



# ARRIS TM804G

## DOCSIS 3.0 CABLE MODEM

### PRODUCT SPECIFICATIONS

#### RF UPSTREAM

Frequency Range (MHz)	5-42
Bonded Channels	Up to 4
Modulation	QPSK, 8 QAM, 16 QAM, 32 QAM, 64 QAM, 128 QAM (S-CDMA only)
Modulation Bandwidth	TDMA: 200, 400, 800, 1600, 3200, 6400 S-CMDA: 1600, 3200, 6400
Data Rate (Mbps Max.)	Up to 122
RF Output Level (dBmV - one channel)	TDMA: +17 to 61 (QPSK) +17 to 58 (8 QAM, 16 QAM) +17 to 57 (32 QAM, 64 QAM) S-CDMA: +17 TO 56 (all modulations)
Automatic Level Adjust	Yes
Frequency Stability (kHz)	±5
Output Impedance (Ohms)	75

#### STANDARDS

DOCSIS® 3.0	RoHS, WEEE
PacketCable® 1.0 and 1.5	IEEE 802.3, IEEE 802.3ab
UL® 60950	RFC3261 SIP: Session Initiation Protocol
FCC Part 15 Class B	Codec: G.711, 64 kbps, $\mu$ -law and A-law encoded speech
CE	Enhanced codec support (G.726, G.728, G.729E)
CB	T.38 Fax Relay