

# CISCO DPC3008

## DOCSIS 3.0 CABLE MODEM

### FEATURES

- 8 bonded downstream channels with data rates in excess of 340 Mbps
- 4 bonded upstream channels with data rates in excess of 120 Mbps
- Designed to meet DOCSIS 3.0 specifications
- Backward compatible with existing DOCSIS 2.0, 1.1, and 1.0 networks
- 10/100/1000 Base-T auto-sensing/auto-MDIX Ethernet port
- Support for up to 64 users (1 USB port user and up to 63 users)
- Dual color LEDs on the front panel
- Remote manageability using SNMP V1/V2 and V3
- Software upgradeable by network download



### PRODUCT SPECIFICATIONS

#### FRONT PANEL FEATURES

##### Indicators

POWER, DS, US, ONLINE, LINK

##### Color

Black case, black face plate, silver text, green/amber LEDs

##### Branding

Cisco and model number

#### BACK PANEL FEATURES

##### Power (Connector Color: Black)

Connects modem to the DC output of the AC power adapter

##### Power Switch (not shown)

Turns power on and off to the device

##### Ethernet (Connector Color: Yellow)

RJ-45 ethernet port connects to the ethernet port on your PC or your home network

##### Reboot EMTA

Power cycles the cable modem

##### Cable (Connector Color: White)

F-connector connects to active cable signal from your service provider



# CISCO DPC3008

## DOCSIS 3.0 CABLE MODEM

### PRODUCT SPECIFICATIONS

#### RF DOWNSTREAM

Operating Frequency Range	88 to 1002 MHz or 54 to 1002 MHz
Tuner Frequency Range	88 to 1002 MHz
Tuner	(1) Frequency agile block tuner, 96 MHz bandpass
Demodulation	8 demodulators, 64 QAM or 256 QAM
Maximum Data Rate	8 downstream channels, each 6 MHz channel: 42.88 Mbps for 256 QAM and 30.34 Mbps for 64 QAM
Bandwidth	6 MHz
Operating Level Range	-15 to +15 dBmV
Input Impedance	75 ohms

#### RF UPSTREAM

Operating Frequency Range	5 to 42 MHz, 5 to 65 MHz or 5 to 85 MHz
Transmitter Frequency Range	5 to 42 MHz, 5 to 65 MHz or 5 to 85 MHz
Upstream Transmission	4 upstream channels
Modulation	A-TDMA: QPSK, 8 QAM, 16 QAM, 32 QAM, 64 QAM S-CDMA: QPSK, 8 QAM, 16 QAM, 32 QAM, 64 QAM, 128 QAM
Bandwidth	200 kHz to 6.4 MHz

# CISCO DPC3008

## DOCSIS 3.0 CABLE MODEM

### PRODUCT SPECIFICATIONS

#### RF UPSTREAM (CONT.)

Maximum Data Rate Per Channel	Modulation	Channel Bandwidth (MHz)	Raw Data Rate (Mbps)
	QPSK	1.6	2.56
	16 QAM	1.6	5.12
	QPSK	3.2	5.12
	16 QAM	3.2	10.24
	32 QAM	3.2	12.8
	64 QAM	3.2	15.4
	16 QAM	6.4	20.5
	32 QAM	6.4	25.6
	64 QAM	6.4	30.72

Maximum Operating Level		One Channel	2 Channels	3 or 4 Channels
TDMA	QPSK	+61 dBmV	+58 dBmV	+55 dBmV
	8 QAM	+58 dBmV	+55 dBmV	+52 dBmV
	16 QAM	+58 dBmV	+55 dBmV	+52 dBmV
	32 QAM	+57 dBmV	+54 dBmV	+51 dBmV
	64 QAM	+57 dBmV	+54 dBmV	+51 dBmV
S-CMDA	QPSK	+56 dBmV	+53 dBmV	+53 dBmV
	8 QAM	+56 dBmV	+53 dBmV	+53 dBmV
	16 QAM	+56 dBmV	+53 dBmV	+53 dBmV
	32 QAM	+56 dBmV	+53 dBmV	+53 dBmV
	64 QAM	+56 dBmV	+53 dBmV	+53 dBmV
	128 QAM	+56 dBmV	+53 dBmV	+53 dBmV



# CISCO DPC3008

**DOCSIS 3.0 CABLE MODEM**

## **PRODUCT SPECIFICATIONS**

### **RF UPSTREAM (CONT.)**

<b>Input Voltage</b>	12 VDC
<b>Power Consumption (Modem Module)</b>	~ 5.0 Watts
<b>Data Ports</b>	Ethernet 10/100/1000 Base-T (Auto-sensing with Auto-MDIX) RJ-45 Ethernet (1)
<b>RF</b>	Female "F" Type
<b>Impedance</b>	75 ohms
<b>Dimensions (H x D x W)</b>	5.92 in. x 4.8 in. 1.15 in. (not including "f" connector)
<b>Weight (Approximate)</b>	8.4 oz.
<b>Operating Temperature °F (°C)</b>	32° to 104°F (0° to 40°C)
<b>Operating Humidity</b>	0 to 90% RH non-condensing
<b>Storage Temperature °F (°C)</b>	-4° to 140°F (-20° to 60°C)
<b>Designed to Comply with the Following Standards</b>	DOCSIS 3.0, 2.0, 1.1, 1.0
<b>Regulatory and Safety Approvals</b>	As required per county where the DPC3008 will be used