



MOTOROLA DCH6200

ANALOG/DIGITAL, HDTV M-CARD™ HOST SET TOP

FEATURES

- M-Card (Multi-stream CableCARD) Host support for conditional access
- Compatible with Motorola DCT legacy APIs
- Standard-definition (SD), enhanced-definition (ED), and high-definition (HD) MPEG-2 video support with output scaled to 480i, 480p, 720p, or 1080i
- Single 54 to 864 MHz video tuner
- Digital video (64 QAM/256 QAM)
- Video scaling (Picture-in-Graphics)
- Accelerated graphics
- Motion-compensating temporal filter video noise reduction
- Motion-adaptive de-interlacing
- Integrated 3-D comb filter for state-of-the-art color and resolution
- Single-channel MPEG-2 encoder for analog content
- Dolby™ Digital 5.1 and PCM audio
- 32 MB Flash (standard)
- 128 MB DRAM total (standard)
- DOCSIS® 2.0 cable modem with support for DSG
- RF out-of-band (OOB) data transmitter/receiver
- On-screen diagnostics
- Macrovision™, HDCP, 5C DTCP, and CGMS-A content protection schemes on the respective interfaces
- Full-featured front panel display and controls



TECHNICAL SPECIFICATIONS

FRONT PANEL

- On/Standby and Message indicators
- Output video format indicator
- 4-character 7-segment display
- IR remote control sensor
- USB 2.0 Host Type A port

REAR PANEL

- F-connector for cable input
- M-Card slot, RF remodulated output (Ch 3/4)
- HDMI output
- YPbPr component output
- Baseband composite video output



MOTOROLA DCH6200

ANALOG/DIGITAL, HDTV M-CARD™ HOST SET TOP

TECHNICAL SPECIFICATIONS

REAR PANEL CONT.

- S-video output
- L/ R audio output
- Coaxial and optical S/PDIF digital audio outputs
- USB 2.0 Host Type A port
- 1394a interfaces (2)
- 10/100 Mbps Ethernet interface
- eSATA interface
- Mini-phone serial port

MANUFACTURING OPTIONAL FEATURES

- M-Card pre-installed, 256 MB DRAM (upgrade from 128 MB)

RF INPUT FREQUENCY

- 54 to 864 MHz

MEMORY

- 32 MB Flash; 128 MB DRAM standard unified
- Legacy platform supported

VIDEO

- Up to 32-bit color, accelerated 2-D support, and scalable video-ingraphics

PROCESSOR

- MIPS, RISC-based

GRAPHICS RESOLUTION

- SD Outputs
 - 4:3 up to 720 x 480
- HD Outputs
 - 16:9 up to 1920 x 1080
- Video Resolution
 - 480i, 480p, 720p, and 1080i

OPERATING TEMPERATURE

- 50° to 108°F (15° to 42°C)

OPERATING HUMIDITY

- 5 to 90% (non-condensing)

AC VOLTAGE

- 105 to 125 VAC, 60 Hz

POWER DISSIPATION

- 42 W (depending on features)

OOB MODULATION

- QPSK
- Frequency
 - Agile receiver 70 to 130 MHz
- Bandwidth
 - 2.0 MHz maximum
- Level
 - -15 to 15 dBmV



MOTOROLA DCH6200

ANALOG/DIGITAL, HDTV M-CARD™ HOST SET TOP

TECHNICAL SPECIFICATIONS

DIGITAL INPUT LEVEL

- 64 QAM
 - -15 to 15 dBmV
- 256 QAM
 - -12 to 15 dBmV

DIMENSIONS

- 2.76 x 17.2 x 12.70 in. (H x W x D)

WEIGHT

- 12.0 lbs.